

## CCSE-DL Participant device long mic, black

### CCS 700



The CCS700 Ultra discussion system is suitable for use in meetings and conference venues with a limited number of participants.

The CCSE-DL delegate units enable participants to actively take part in the meeting proceedings. A built-in microphone allows them to speak to the other delegates, and they can listen to the discussion using the built-in loudspeaker or (optional) personal headphones.

#### Functions

##### Microphone with flexible stem and light ring

The microphone has a flexible stem, which is easily adjustable to suit personal preferences. It also allows two people to use the same delegate unit as they can pull the microphone towards them, when it is required to speak. The microphone is fixed to the base of the delegate unit. Incorporated into the head of the microphone is a light ring which illuminates red when the microphone is on.

##### Built-in loudspeaker

Loudspeaker volume is set centrally at the control unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

##### Two headphone sockets

Two 3.5 mm (0.14 in) stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit.

- ▶ Compact, attractive design
- ▶ Built-in volume control for headphones
- ▶ Microphone with flexible stem and light ring
- ▶ Two headphone sockets

##### Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

##### Controls and Indicators

- Microphone on/off button.
- Rotary volume control for adjusting headphone volume.
- Loudspeaker, automatically muted when microphone is on.
- Microphone 'on' indicator (red LED).
- Light ring indicator on microphone stem, lights up red when microphone is on.

##### Interconnections

- 1 x 2.7 m (106.3 in) cable terminated with a 8-pin male connector for loop-through connection to other.
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairman units.
- 2 x 3.5 mm (0.14 in) stereo headphone sockets.

#### Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

#### Parts included

Quantity	Component
1	CCSE-DL Chairperson device long mic, black base

## Technical specifications

### Electrical

Nominal Acoustic Input at the microphone	85dB SPL
Frequency Response	400Hz to 10Khz

### Mechanical

Dimensions (without microphone) (H x W x D)	54x136x138mm
Length of the microphone from the base of the stem	488mm
Weight	1.2 kg
Mounting	Tabletop
Color	Charcoal

### Environmental

Operating temperature	-5 °C to +45 °C
Storage temperature	-40 °C to +70 °C

## Ordering information

**CCSE-DL Participant device long mic, black**  
 Chairperson device long mic, black base  
 Order number **CCSE-DL | F.01U.294.075**

### Accessories

**CCSE-CA10 Extension cable, 10m**  
 CCS700 Extension cable assembly - 10m  
 Order number **CCSE-DL | F.01U.309.729**

#### Represented by:

**Europe, Middle East, Africa:**  
 Bosch Security Systems B.V.  
 P.O. Box 80002  
 5600 JB Eindhoven, The Netherlands  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Germany:**  
 Bosch Sicherheitssysteme GmbH  
 Robert-Bosch-Platz 1  
 D-70839 Gerlingen  
[www.boschsecurity.com](http://www.boschsecurity.com)

**North America:**  
 Bosch Security Systems, LLC  
 130 Perinton Parkway  
 Fairport, New York, 14450, USA  
[www.boschsecurity.com](http://www.boschsecurity.com)

**Asia-Pacific:**  
 Robert Bosch (SEA) Pte Ltd, Security Systems  
 11 Bishan Street 21  
 Singapore 573943  
[www.boschsecurity.com/xc/en/contact/](http://www.boschsecurity.com/xc/en/contact/)  
[www.boschsecurity.com](http://www.boschsecurity.com)